

APD 25 A

Aksa
Aksa
P 602

Manufacturer		Aksa						
Model		A4CRX25						
		<table border="1"> <tr> <td>% \$ \$</td> <td>"# "</td> </tr> <tr> <td>α(ΔΔΔ</td> <td></td> </tr> <tr> <td>0 & Z</td> <td>\$ < DQ</td> </tr> </table>	% \$ \$	"# "	α(ΔΔΔ		0 & Z	\$ < DQ
% \$ \$	"# "							
α(ΔΔΔ								
0 & Z	\$ < DQ							
	L	2,540						
	"	90 X 100						
		18.0:1						
	fl # 7	"# " 1500						
	fl 7	L 8,50						
		L 11,00						
AbsorbedAirDischargeReSourceKey.Text	' # "	1,90						
	' # "	113,00						
	' # "	5,00						
	° C	480,00						
		12 V d.c.						
	Load	% \$ \$						
	# "							
		5,50						

		Aksa
		AK218
	Hz	50
	"	22,50
7 cg'		0,80
		3
	fl 7	400/230
	A	32,00

		fl 7		fl 7	
	"	"	"	"	L
APD 25 A	665,00	1500,00	900,00	1060,00	95,00
		fl 7		fl 7	
	"	"	"	"	L
ASM 3	790.00	1940	970	1220	95

APD 25 A

Aksa
Aksa P 602

9B: #9
 9b[]bY'gdYYX"
 C]'dfYggi fY"
 7cc'UbhY'a dYfUhi fY"
 F i b' hja Y"
 6UHYfmj c'rg"
 7cbZ[i fUVY' hja]b["
 ; 9B9F 5HCF
 J c' HU[Y f@ @B' "
 7i ffYbhf@&!@ E"
 : fYei YbVW"
 A 5-BG
 J c' HU[Y f@ @B' "
 : fYei YbVW"
 A U]bg'fYUXn"
 A U]bg'YbUV'YX"
 ; Yb"GYhfYUXn"
 ; Yb"GYhYbUV'YX"

K 5F B-B:
 7\UF[Y Z]i fY"
 6UHYfm@ck #:[\] c' HU[Y"
 : U] 'hc' ghd"
 @ck #:[\] [YbYfUhc'f'j c' HU[Y"
 I bXYf#j Yf[YbYfUhc'f'ZfYei YbVW"
 Cj Yf# bXYf'gdYYX"
 @ck c]'dfYggi fY"
 <][\ V'c'UbhY'a dYfUhi fY"
 G<I H8CK BG
 : U] 'hc' gHU"
 9a Yf[YbVW'ghcd"
 @ck c]'dfYggi fY"
 <][\ V'c'UbhY'a dYfUhi fY"
 Cj Yf# bXYf'gdYYX"
 I bXYf#j Yf[YbYfUhc'f'ZfYei YbVW"
 I bXYf#j Yf[YbYfUhc'f' c' HU[Y"
 C]'dfYggi fY'gYbgcf'cdYb"
 7cc'UbhY'a dYfUhi fY'gYbgcf'cdYb"
 9@97 HF =75@HF -D
 ; YbYfUhc'f'c'j YfW'ffYbh"

: 'YI J'V'Y'gYbgcf'WVb VY V'c'bfcc'YX'k]h' h'Ya dYfUhi fYz
 dfYggi fYz dYfVW'bhU[Y f'k Ufb]b[#]i h'Xck b#Y'VW'VW' h'f'dL
 @c'WV'gYh]b['dUfUa YHfg'UbX'a cb]h'f]b['Zca 'D7 'hc
 V'c'bfcc' a cXi 'Y'k]h' I G6 V'c'bbYVW'cb'fa Ul '* 'a H'

9'YVW'VW' GUZYhm#9A 7 'V'a dUH[V]]hm6G'9B '* \$-) \$
 9'YVW'VW' Vi g]bYgg'Yei]da Ybh'
 6G'9B '*%\$!*&9A 7 'ja a i b]mighUbXUfX"
 6G'9B '*%\$!*('9A 7 'Ya]gg]cb'ghUbXUfX"

'6UHYfmVXUf[Yf]g'a Ubi ZVW' fYX'k]h' 'gk]h'W]b[!a cXY'UbX'GA 8 'YVW'bc'c[mUbX'ih\Ug\][\ YZ]VbYVW' 6UHYfmVXUf[Yf
 a cXY'gfci hdi hJ !=VXUfUW'f]gh]W]g'j YfmV'cgY'hc'gei UfY'UbX'ci hdi h]g']'Ua dYfz% z']'Zcf'%&j c'hUbX'&+Z']'Zcf'&'(]'
 #bdi h% , ' !&* (j c'h57 "" Dfc]bY'&(\$) \Ug'Z' mci hdi hg\chV'VW]hdfchVW]cb'UbX'ihVWb VY i gYX'Ug'U'W'ffYbhgci fVW"
 Dfc]bY'&(\$) #&(\$) V'XUf[Yf'\Ug'\][\ YZ]VbYVW'cb["]Z'Z' 'ck ZU]i fY'fUfYz'][\hk Y][\hUbX'ck \YUhfUX]UfYX']b
 UVV'cfXUbW'k]h']'bYUf'U'fYfbU]j Yg' H\Y'VXUf[Yf]g'Z'hYX'k]h' U'dfchVW]cb'X]cXY'UV'cgg'h'Y'ci hdi h'7 cbbYVW'VXUf[Y'Z]
 fY'UmV'c] VYhk Yyb'dcg]h]j Y'ci hdi hUbX'7: 'ci hdi h' H\Y'mUfY'Yei]ddYX'k]h' F: =Z]h'f'hc'fYXi V'Y'YVW'VW'bc]gY'fUX]UfYX
 Zca 'h'Y'XYj]V'"; Uj Ub]W' m]gc'UfYX']bdi hUbX'ci hdi h]m]d]VW'm(_J 'Zcf'\][\ fY']UV]]h'f

APD 25 A

Aksa
Aksa P 602

5GA " !'



- 1 Steel structures.
- 2 Emergency stop push button.
- 3 Control panel is mounted on the baseframe . Located at the right side of the generator set.
- 4 Corrosion-resistant locks and hinges.
- 5 oil could be drained via valve and a hose
- 6 Exhaust system in the canopy.
- 7 special large access doors for easy maintenance
- 8 Base frame -fuel tank.
- 9 Lifting Points.
- 10 sound proofing materials.

f) !&+)

ž

ž

ž

ž

ž

ž

ž

	"	970
f) "L	"	1940
f) "L	"	1220
	L	95